

基本尺寸				基本额定负荷		极限转速		轴承代号	作用点a	安装相关尺寸			重量
d	D	B	r12	Cr	Cor	脂润滑	油润滑			da(min)	Da(max)	ra(max)	
35	72	27	1.1	32.5	35	6500	8000	3207M	46.3	39	68	1	0.51
45	85	30.2	1.1	50.7	46	5000	6700	3209M	53.5	52	78	1	0.719
45	85	30.2	1.1	50.7	46	5000	6700	3209F1/C3	53.5	52	78	1	0.71
55	100	33.3	1.5	54	47	4500	5800	3211ATN1/V1	60.2	63	96	1.5	0.99
60	110	36.5	1.5	82.6	81	3800	5000	3212M	69.7	69	101	1.5	1.47
65	120	38.1	1.5	91	96	3600	4500	3213YM	64.7	74	111	1.5	1.84
65	120	38.1	1.5	51	60	3600	4500	3213ATN1/V1	71.8	74	111	1.5	1.7
65	140	58.74	2.1	164	150	3200	4300	3313DYM	79.4	77	128	2	4.89
75	130	41.3	1.5	111	119	3200	4300	3215DYM	70.6	84	121	1.5	2.81
75	130	41.3	1.5	107	115	3200	4300	3215	73	84	121	1.5	2.09
75	160	68.3	2.1	208	197	3000	4100	3315DYM	91.5	87	148	2	6.82
75	160	68.3	2.1	203	191	3000	4100	3315	103.8	87	148	2	6.27
80	170	68.3	2.1	221	216	2800	3600	3316M	105.6	92	158	2	7.21
100	180	60.3	2.1	198	215	2000	2700	3220YM	129.5	112	168	2	6.46
110	240	92.1	3	358	429	1800	2400	3322M	151	124	226	2.5	19.9
120	190	66	2	179	237	2500	3600	4024X3DM/W34	130.1	133	175.8	2	6.78
130	200	75	2	150	200	2200	3200	4026X2DM	202.5	140	190	2	8.29
150	225	73	2	199	275	2200	3200	4030X2DYM/YA6W34	193.8	164	212	2	6.78
150	230	70	2.1	185	250	2200	3200	4030X3DM	200.1	162	218	2	10.7
160	240	76	2.1	225	315	1900	2500	4032X2M/DCYA1	129.9	172	228	2	12.5
160	240	80	2.1	210	289	1900	2500	4032DM	240	172	228	2	12.2
160	240	80	2.1	210	289	1900	2500	4032DM/C91W33A	239.8	172	228	2	12.2
170	260	84	2.1	207	385	1600	2100	4034X2BM/YA1	138.5	182	248	2	16.2
170	260	90	2.1	250	355	1600	2100	4034DM	260	182	248	2	16.9
180	259.5	66	2.1	281	313	1400	1800	4936X3DM	253	192	248	2	10.8
180	259.5	66	2.1	216	312	1400	1800	4936X3DM/W33	253	192	248	2	10.7
180	259.5	66	2.1	281	313	1400	1800	4936X3DM/W34	253	192	248	2	10.7
180	280	100	2.1	275	400	1300	1700	4036DM/C9W33	280	192	268	2	22.4
180	280	100	2.1	275	400	1300	1700	4036DM/W33	280	192	268	2	22.4
190	269.5	66	2.1	220	324	1350	1700	4938X3DM	262.7	202	258	2	11.5
190	269.5	66	2.1	220	324	1350	1700	4938X3DM/W34	262.7	202	258	2	11.5

200	310	109	2.1	343	538	1200	1600	4040DM/W34	309.5	212	298	2	28
220	309.5	76	2.1	250	381	1100	1500	4944X3DM	303	232	298	2	18
220	340	118	3	359	596	1000	1400	4044DM/W34	339	234	326	2.5	38.8
220	340	118	3	385	645	1000	1400	4044/DCYA1	118	234	326	2.5	39.6
240	360	118	3	470	650	900	1250	4048DM/W33	359	254	346	2.5	42.8
240		118	3	376	648	900	1250	4048X1DM/W34	359	254	346	2.5	44.9
240		118	3	470	650	900	1250	4048X1DM/C9W33	359	254	346	2.5	42.5
260	369.5	92	4	373	662	800	1200	4952X3DM/W34	361	278	352	3	31.3
260	369.5	92	4	373	662	800	1200	4952X3DM	361	278	352	3	31.3
260	400	130	4	470	855	800	1100	4052X2/DCYA1	212	278	382	3	60.2
260	400	140	4	450	830	800	1100	4052DM	400	278	382	3	62
260	400	140	4	450	830	800	1100	4052DM/C9W33	400	278	382	3	62
280	389.5	92	4	377	683	750	1100	4956X3DM/W34-1	381	298	372	3	34
300	419.5	112	2.1	423	791	700	1000	4960X3DM	416	342	408	2	43
300	460	160	4	569	1149	640	960	4060DYM	398.6	348	442	3	97.9
320	440	112	2.1	460	920	630	850	4964X2DM/W33	374.9	332	428	2	53.2